

BUMERANG

Sound-absorbing screens



Today, office landscapes are often used in public as well as private enterprises. Unfortunately, this often brings along a high noise level, as a consequence of colleagues' telephone conversations and meetings with customers, only at a very short distance. It can be comfortable to screen off your working area with Akustikmiljö's flexible office screens. There are many models and they are available as screens standing on the floor or fixed to the table. Width 950 mm, adjustable height 1400–1600 mm. Both frames and absorbents are available in a number of colours with visible, lacquered frames or, alternatively, other models with hidden frames. With their excellent acoustic qualities, they provide both efficient and decorative framing of the working area.

An efficient and decorative office solution, preventing reverberation of sound between working areas.

Design: Andreas Klippinge / Hyllteknik AB

Akustikmiljö's flexible sound-absorbing office screens have a number of shelves, consoles and wheels as optional choices and can also be used as notice-boards.



JAN. 2009



Designation when ordering

“Akustikmiljö sound-absorbing screens”.

Size, W x H, foot, wheels or table attachment, colour.

Cleaning

The absorbents are best cleaned with a dry brush, a vacuum-cleaner, a blower or, as an alternative, wet cleaning with cold water, a clean cloth and environment-friendly washing or cleaning detergents.

Product information

- Sound absorbent made of 100 % polyester fibre.
- Under the trade mark Sund® the fibre has been used by Akustikmiljö for several years as subceiling and sound absorbent.
- Can withstand moisture, is scentless and does not rot or mould.
- No glue or adhesives.
- Does not provide any measurable emissions, is not allergenic, skin sensitizing or irritating to the respiratory passages.
- Since the 1960's, the fibre has been used for textile purposes as well as for many applications within the medical service, without any problems.

Fire-technical qualities

With Trevira CS surface the absorbent has been tested by the Swedish SP according to SS-EN ISO 11925-2.

Acoustic qualities

Performed by the Swedish SP according to ISO 354 and ISO 11654

Product	Surface	Frekvens Hz						
		63	125	250	500	1'	2'	4'
Bumerang	Trevira CS	0,05	0,30	0,60	0,95	1,0	0,95	0,85

Akustikmiljö was started in 1996 and today is one of the leading companies within the acoustic trade. Akustikmiljö's business concept is to design sound-improving solutions aimed for anything from modern settings designed by architects and music studios to K-labelled (under national protection) seventeenth century buildings. Akustikmiljö's head office and production plant are found in Falkenberg, Sweden, and we deliver solutions to a number of countries all over Scandinavia and parts of Europe.



akustikmiljö