

TRIPLE ABSORBENT MinimiZer®



TRIPLE ABSORBENT is part of a series with sound-absorbing panels of various shapes, presented under the umbrella term **MinimiZer®**, standing for quality and a good absorption capacity. The core material of our absorbents is 100 % polyester fibre, which is also used in our **SUND®** environment absorbents and subceilings.

TRIPLE ABSORBENT is a broad band absorbent designed for wall installation. The absorbent has the form of a triangle with the base 425 mm, height 1200 mm and depth 200 mm.

The products are excellent for use in home, studio, office or school settings. **TRIPLE ABSORBENT** incredibly efficiently reduces side reverberations thanks to it sticking out 220 mm from the wall. The absorbents are provided with top

and bottom of white or black lacquered steel and a laminated surface in a number of colours and patterns. If you wish to have your own surface design, we can laminate that too.

The absorbent is delivered as:

- Form cut absorbents with the surface laminated and with top and bottom for attachment against the wall.



JAN. 2009



Designation when ordering

“Akustikmiljö TRIPLE ABSORBENT”:

Art. No. 430011 MinimiZer® TRIPLE ABSORBENT 1200 x 425 x 220, surface Trevira CS.

Art. No. 431011 MinimiZer® TRIPLE ABSORBENT 1200 x 425 x 220, surface PBS Cambrelle, alternatively CM.

Art. No. 432011 MinimiZer® TRIPLE ABSORBENT 600 x 425 x 220 with back piece and floor pads for floor reverberations.

Cleaning

The absorbents are best cleaned with a dry brush, a vacuum-cleaner, a blower or, as an alternative, wet cleaning with cold water, a clean cloth and environment-friendly washing or cleaning detergents.

Fire-technical qualities

With Akustikmiljö's standard surface TRIPLE ABSORBENT fulfils the fire-technical requirements for surfaces class 1, (B-s1,d0).

Product information

- Sound absorbent made of 100 % polyester fibre.
- Under the trade mark Sund® the fibre has been used by Akustikmiljö for several years as subceiling and sound absorbent.
- Can withstand moisture, is scentless and does not rot or mould.
- No glue or adhesives.
- Does not provide any measurable emissions, is not allergenic, skin sensitizing or irritating to the respiratory passages.
- Since the 1960's, the fibre has been used for textile purposes as well as for many applications within the medical service, without any problems.

Acoustic qualities

Performed by the Swedish SP according to ISO 354 and ISO 11654

Product	Surface	Constr. height	Frequency Hz						
			63	125	250	500	1'	2'	4'
Triple	Triangle	220	0,10	0,40	0,50	0,80	0,80	0,80	0,60
50 mm	Trevira CS								

Akustikmiljö was started in 1996 and today is one of the leading companies within the acoustic trade. Akustikmiljö's business concept is to design sound-improving solutions aimed for anything from modern settings designed by architects and music studios to K-labelled (under national protection) seventeenth century buildings. Akustikmiljö's head office and production plant are found in Falkenberg, Sweden, and we deliver solutions to a number of countries all over Scandinavia and parts of Europe.



akustikmiljö